



VISCOTAQ® Sealing System

Fast and easy sealing of
highly complicated and
irregular molded parts



Non-hardening sealant for
penetrations

Water- and gas tight



Construction



Contractor



Water



VVS



Energy



Oil



Gas



Industry

VISCOTAQ® ViscoSealant - Cartridge

Area of application:

Sealant for concrete, steel, PVC, metal, wood, vinyl and other coatings; Pipe and Cable wall penetrations/multiple penetrations; Sealing of gravity lines, manholes, tank bottoms, seams and cracks; Complicated and irregular shape parts for underground as well as above ground use.

Material:

Semi-solid polyolefin sealant (paste-like)

Egenskaber

Impervious to moisture and gases; self-healing; resistant to e.g.: Acids and salts; fast long-term protective coating; non-toxic; non-flammable - contains fire retardant and self-extinguishing materials; UV-resistant; no cracking or embrittlement; frost and thaw resistant; conforms to irregular shapes; heat resistance: -45°C to +71°C.

Complies with NACE 0109:2019 og ISO 21809-3:2016

Sizes:

Cartridge; 310 ml

PRODUCT INFORMATION

Properties:

- Impervious to water and gas
- VISCOTAQ® contains no solvents, no carcinogenic substances - non-toxic
- VISCOTAQ® fire retardant and self-extinguishing - non-flammable
- No primer or mixing required
- Minimal surface preparation (SP2-wire brush)
- Inert material, no deterioration over time
- Flexible
- Adhesion to almost all surfaces
- Long shelf life depending on type of storage and condition of packaging

Area of application:

- Specially designed for a wide range of applications and temperatures for filling cavities and leveling irregular surfaces
- Protects against moisture, gas and bacteria penetration

Description:

- ViscoSealant is a viscous, elastic, non-hardening sealing compound for sealing and as corrosion protection

Notes:

- It is recommended to store the product at +20°C to +30°C for 24 hours prior to use to ensure optimum application properties
- Unlimited shelf life in containers are not opened and stored in well-ventilated areas at temperatures +4°C og +60°C

SUITABLE ACCESSORIES

Cartridge gun



Mortar



Foam tape, roll

